

AX6000 8-Stream Wi-Fi 6 VoIP Router

MODEL: EX820v



Overview

The EX820v is TP-Link wireless router with Wi-Fi 6 – based on the New Era 802.11ax Wi-Fi technology. Take your Wi-Fi to the next level while being backwards compatible with 802.11a/b/g/n/ac Wi-Fi standards.



AX6000 Dual Band Wi-Fi

Deliver total Wi-Fi speeds up to 6 Gbps (4804 Mbps on 5 GHz, 1148 Mbps on 2.4 GHz) based on 802.11ax Wi-Fi technology.



2.5G Internet Connection

Boost whole internet throughput up to 2.5 Gbps for more smooth and faster online activities. Three gigabit Ethernet LAN ports and one USB 3.0 port also help to transfer data at blistering speeds.



Supports VoIP Calls

With two FXS ports, users can make or receive phone calls over the internet simply by connecting the device to their existing telephone set.



Easy Remote Management

TR-069 and TR-369 protocols, Aginet app, and TAUC (TP-Link Aginet Unified Cloud) are supported, service providers can manage multiple devices remotely.



Specifications

Hardware

Interface

1× 10/100/1000/2500 Mbps RJ45 WAN Port,

1× 10/100/1000/2500 Mbps RJ45 LAN Port,

3× 10/100/1000 Mbps RJ45 LAN Ports,

2× FXS Ports, 1× USB 3.0 Port

OR

1× 10/100/1000/2500Mbps SPF+ Port,

1× 10/100/1000/2500Mbps WAN/LAN Port,

3× 10/100/1000Mbps LAN Port,

2× FXS Ports, 1× USB 3.0 Port

Button

Power On/Off Button, Reset Button, Wi-Fi Button, WPS Button

• External Power Supply

12V/2.5A

• Dimensions (W * D * H)

8.46 × 6.86 × 2.46 in (214.9 × 174.3 × 62.6 mm)

• CPU

2 GHz AMR Quad-Core CPU

Antenna

Internal Wi-Fi antennas

Wireless

Wireless Standards

IEEE 802.11a/n/ac/ax 5 GHz, IEEE 802.11b/g/n/ax 2.4 GHz

• Mesh Protocol

802.11k/v/r

Frequency

2.4 GHz and 5 GHz

Signal Rate

4804Mbps at 5 GHz, 1148 Mbps at 2.4 GHz

• Transmit Power

CE: <20dBm (2.4GHz); <23dBm (5.15GHz~5.35GHz); <30dBm (5.47GHz~5.725GHz)

• Wireless Function

Enable/Disable Wireless Radio, WMM, Wireless Statistics, Multi-SSID, Guest Network

Wireless Security

WPA/WPA2/WPA3 Personal, WPA/WPA2 Enterprise

• Wireless Schedule

Support 2.4 GHz and 5 GHz Wireless Schedule

Support EasyMesh

Others

System Requirements

Microsoft Windows 98SE, NT, 2000, XP, VistaTM or Windows 7, 8, 8.1,10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browers or higher.

Certification

CE, DFS

Software

• DHCP

Server, DHCP Client List, Address Reservation

Operation Mode

Router Mode

WAN Type

Dynamic IP/Static IP/PPPoE/PPTP/L2TP/Bridge Multi-EWAN

Management

Local management: WebGUI management, Aginet app management Remote management: TR-069, TR-181, TR369, TR-111, TR-143 Cloud management: TAUC

Features

Parental Control, QoS (Quality of Service), Address Reservation, Port Forwarding, Cloud Upgrade, EasyMesh , IPv6, NAT Forwarding, Firewall, Network Diagnosic, CWMP, Traffic Statistic,1024-QAM, MU-MIMO, OFDMA, IPSEC VPN

Port Forwarding

Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS

NO-IP, DynDNS

VPN Server

PPTP, OpenVPN, IPSec

VPN Pass-through

IPSec, PPTP, L2TP

Access Control

Parental Control, Local Management, Host List, White/Black List

Firewall Security

DoS, SPI Firewall, IP and MAC Address Binding

Protocols

Supports IPv4 and IPv6

USB Sharing

Supports Storage/FTP Server/Media Server

• Multi-SSID

Up to 3 SSIDs for each band (including main SSID)

• Support VoIP

Environment

Operating Temperature: 0°C~40°C (32°F~104°F), Storage Temperature: -40°C~60°C (-40°F ~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Package Contents

AX6000 8-Stream Wi-Fi 6 VoIP Router EX820v

1× RJ45 Ethernet Cable 1× Power Adapter

1× RJ11 Cable

1× Quick Installation Guide